

Bus 005 Device 002: ID 0c45:6270 Microdia PC Camera (SN9C201 + MI0360/MT9V011 or MI0360SOC/MT9V111) U-CAM PC Camera NE878, Whitcom WHC017, ...

Device Descriptor:

```

bLength          18
bDescriptorType  1
bcdUSB           2.00
bDeviceClass     0 (Defined at Interface level)
bDeviceSubClass  0
bDeviceProtocol  0
bMaxPacketSize0 64
idVendor         0x0c45 Microdia
idProduct        0x6270 PC Camera (SN9C201 + MI0360/MT9V011 or MI0360SOC/MT9V111) U-CAM PC Camera
NE878, Whitcom WHC017, ...
bcdDevice        1.00
iManufacturer    0
iProduct         1 USB20 Camera
iSerial          0
bNumConfigurations 1

```

Configuration Descriptor:

```

bLength          9
bDescriptorType  2
wTotalLength     279
bNumInterfaces   1
bConfigurationValue 1
iConfiguration   0
bmAttributes     0x80
                (Bus Powered)
MaxPower         500mA

```

Interface Descriptor:

```

bLength          9
bDescriptorType  4
bInterfaceNumber 0
bAlternateSetting 0
bNumEndpoints   3
bInterfaceClass  255 Vendor Specific Class
bInterfaceSubClass 255 Vendor Specific Subclass
bInterfaceProtocol 255 Vendor Specific Protocol
iInterface       0

```

Endpoint Descriptor:

```

bLength          7
bDescriptorType  5
bEndpointAddress 0x81 EP 1 IN
bmAttributes     1
                Transfer Type Isochronous
                Synch Type None
                Usage Type Data
wMaxPacketSize  0x0000 1x 0 bytes
bInterval        1

```

Endpoint Descriptor:

```

bLength          7
bDescriptorType  5
bEndpointAddress 0x82 EP 2 IN
bmAttributes     2
                Transfer Type Bulk
                Synch Type None
                Usage Type Data
wMaxPacketSize  0x0200 1x 512 bytes
bInterval        0

```

Endpoint Descriptor:

```

bLength          7
bDescriptorType  5
bEndpointAddress 0x83 EP 3 IN
bmAttributes     3
                Transfer Type Interrupt
                Synch Type None
                Usage Type Data
wMaxPacketSize  0x0001 1x 1 bytes
bInterval        10

```

Interface Descriptor:

```

bLength          9
bDescriptorType  4

```

```

bInterfaceNumber      0
bAlternateSetting     1
bNumEndpoints        3
bInterfaceClass       255 Vendor Specific Class
bInterfaceSubClass    255 Vendor Specific Subclass
bInterfaceProtocol    255 Vendor Specific Protocol
iInterface            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x81 EP 1 IN
  bmAttributes         1
    Transfer Type      Isochronous
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0080 1x 128 bytes
  bInterval            1
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x82 EP 2 IN
  bmAttributes         2
    Transfer Type      Bulk
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0200 1x 512 bytes
  bInterval            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x83 EP 3 IN
  bmAttributes         3
    Transfer Type      Interrupt
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0001 1x 1 bytes
  bInterval            10
Interface Descriptor:
  bLength              9
  bDescriptorType      4
  bInterfaceNumber     0
  bAlternateSetting     2
  bNumEndpoints        3
  bInterfaceClass       255 Vendor Specific Class
  bInterfaceSubClass    255 Vendor Specific Subclass
  bInterfaceProtocol    255 Vendor Specific Protocol
  iInterface            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x81 EP 1 IN
  bmAttributes         1
    Transfer Type      Isochronous
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0100 1x 256 bytes
  bInterval            1
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x82 EP 2 IN
  bmAttributes         2
    Transfer Type      Bulk
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0200 1x 512 bytes
  bInterval            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x83 EP 3 IN
  bmAttributes         3

```

```

    Transfer Type          Interrupt
    Synch Type            None
    Usage Type           Data
    wMaxPacketSize       0x0001  1x 1 bytes
    bInterval            10
Interface Descriptor:
  bLength                9
  bDescriptorType        4
  bInterfaceNumber       0
  bAlternateSetting      3
  bNumEndpoints          3
  bInterfaceClass        255 Vendor Specific Class
  bInterfaceSubClass     255 Vendor Specific Subclass
  bInterfaceProtocol     255 Vendor Specific Protocol
  iInterface             0
Endpoint Descriptor:
  bLength                7
  bDescriptorType        5
  bEndpointAddress       0x81  EP 1 IN
  bmAttributes           1
    Transfer Type        Isochronous
    Synch Type           None
    Usage Type           Data
  wMaxPacketSize        0x0180  1x 384 bytes
  bInterval              1
Endpoint Descriptor:
  bLength                7
  bDescriptorType        5
  bEndpointAddress       0x82  EP 2 IN
  bmAttributes           2
    Transfer Type        Bulk
    Synch Type           None
    Usage Type           Data
  wMaxPacketSize        0x0200  1x 512 bytes
  bInterval              0
Endpoint Descriptor:
  bLength                7
  bDescriptorType        5
  bEndpointAddress       0x83  EP 3 IN
  bmAttributes           3
    Transfer Type        Interrupt
    Synch Type           None
    Usage Type           Data
  wMaxPacketSize        0x0001  1x 1 bytes
  bInterval              10
Interface Descriptor:
  bLength                9
  bDescriptorType        4
  bInterfaceNumber       0
  bAlternateSetting      4
  bNumEndpoints          3
  bInterfaceClass        255 Vendor Specific Class
  bInterfaceSubClass     255 Vendor Specific Subclass
  bInterfaceProtocol     255 Vendor Specific Protocol
  iInterface             0
Endpoint Descriptor:
  bLength                7
  bDescriptorType        5
  bEndpointAddress       0x81  EP 1 IN
  bmAttributes           1
    Transfer Type        Isochronous
    Synch Type           None
    Usage Type           Data
  wMaxPacketSize        0x0200  1x 512 bytes
  bInterval              1
Endpoint Descriptor:
  bLength                7
  bDescriptorType        5
  bEndpointAddress       0x82  EP 2 IN
  bmAttributes           2
    Transfer Type        Bulk
    Synch Type           None

```

```

    Usage Type          Data
    wMaxPacketSize      0x0200 1x 512 bytes
    bInterval           0
Endpoint Descriptor:
    bLength              7
    bDescriptorType      5
    bEndpointAddress     0x83 EP 3 IN
    bmAttributes         3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize      0x0001 1x 1 bytes
    bInterval           10
Interface Descriptor:
    bLength              9
    bDescriptorType      4
    bInterfaceNumber     0
    bAlternateSetting    5
    bNumEndpoints        3
    bInterfaceClass      255 Vendor Specific Class
    bInterfaceSubClass   255 Vendor Specific Subclass
    bInterfaceProtocol   255 Vendor Specific Protocol
    iInterface           0
Endpoint Descriptor:
    bLength              7
    bDescriptorType      5
    bEndpointAddress     0x81 EP 1 IN
    bmAttributes         1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize      0x02a8 1x 680 bytes
    bInterval            1
Endpoint Descriptor:
    bLength              7
    bDescriptorType      5
    bEndpointAddress     0x82 EP 2 IN
    bmAttributes         2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize      0x0200 1x 512 bytes
    bInterval            0
Endpoint Descriptor:
    bLength              7
    bDescriptorType      5
    bEndpointAddress     0x83 EP 3 IN
    bmAttributes         3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize      0x0001 1x 1 bytes
    bInterval            10
Interface Descriptor:
    bLength              9
    bDescriptorType      4
    bInterfaceNumber     0
    bAlternateSetting    6
    bNumEndpoints        3
    bInterfaceClass      255 Vendor Specific Class
    bInterfaceSubClass   255 Vendor Specific Subclass
    bInterfaceProtocol   255 Vendor Specific Protocol
    iInterface           0
Endpoint Descriptor:
    bLength              7
    bDescriptorType      5
    bEndpointAddress     0x81 EP 1 IN
    bmAttributes         1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize      0x0320 1x 800 bytes

```

```

    bInterval          1
Endpoint Descriptor:
    bLength           7
    bDescriptorType   5
    bEndpointAddress  0x82 EP 2 IN
    bmAttributes      2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize    0x0200 1x 512 bytes
    bInterval         0
Endpoint Descriptor:
    bLength           7
    bDescriptorType   5
    bEndpointAddress  0x83 EP 3 IN
    bmAttributes      3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize    0x0001 1x 1 bytes
    bInterval         10
Interface Descriptor:
    bLength           9
    bDescriptorType   4
    bInterfaceNumber  0
    bAlternateSetting 7
    bNumEndpoints     3
    bInterfaceClass   255 Vendor Specific Class
    bInterfaceSubClass 255 Vendor Specific Subclass
    bInterfaceProtocol 255 Vendor Specific Protocol
    iInterface        0
Endpoint Descriptor:
    bLength           7
    bDescriptorType   5
    bEndpointAddress  0x81 EP 1 IN
    bmAttributes      1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize    0x0b84 2x 900 bytes
    bInterval         1
Endpoint Descriptor:
    bLength           7
    bDescriptorType   5
    bEndpointAddress  0x82 EP 2 IN
    bmAttributes      2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize    0x0200 1x 512 bytes
    bInterval         0
Endpoint Descriptor:
    bLength           7
    bDescriptorType   5
    bEndpointAddress  0x83 EP 3 IN
    bmAttributes      3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize    0x0001 1x 1 bytes
    bInterval         10
Interface Descriptor:
    bLength           9
    bDescriptorType   4
    bInterfaceNumber  0
    bAlternateSetting 8
    bNumEndpoints     3
    bInterfaceClass   255 Vendor Specific Class
    bInterfaceSubClass 255 Vendor Specific Subclass
    bInterfaceProtocol 255 Vendor Specific Protocol
    iInterface        0
Endpoint Descriptor:

```

```

    bLength                7
    bDescriptorType        5
    bEndpointAddress      0x81 EP 1 IN
    bmAttributes           1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize        0x1400 3x 1024 bytes
    bInterval              1
Endpoint Descriptor:
    bLength                7
    bDescriptorType        5
    bEndpointAddress      0x82 EP 2 IN
    bmAttributes           2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize        0x0200 1x 512 bytes
    bInterval              0
Endpoint Descriptor:
    bLength                7
    bDescriptorType        5
    bEndpointAddress      0x83 EP 3 IN
    bmAttributes           3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize        0x0001 1x 1 bytes
    bInterval              10
Device Qualifier (for other device speed):
    bLength                10
    bDescriptorType        6
    bcdUSB                 2.00
    bDeviceClass           0 (Defined at Interface level)
    bDeviceSubClass        0
    bDeviceProtocol        0
    bMaxPacketSize0        64
    bNumConfigurations     1
Device Status:           0x0000
    (Bus Powered)

Bus 005 Device 002: ID 0c45:6270 Microdia PC Camera (SN9C201 + MI0360/MT9V011 or MI0360SOC/MT9V111) U-
CAM PC Camera NE878, Whitcom WHC017, ...
Device Descriptor:
    bLength                18
    bDescriptorType        1
    bcdUSB                 2.00
    bDeviceClass           0 (Defined at Interface level)
    bDeviceSubClass        0
    bDeviceProtocol        0
    bMaxPacketSize0        64
    idVendor               0x0c45 Microdia
    idProduct              0x6270 PC Camera (SN9C201 + MI0360/MT9V011 or MI0360SOC/MT9V111) U-CAM PC Camera
    NE878, Whitcom WHC017, ...
    bcdDevice              1.00
    iManufacturer          0
    iProduct               1 USB20 Camera
    iSerial                 0
    bNumConfigurations     1
Configuration Descriptor:
    bLength                9
    bDescriptorType        2
    wTotalLength           279
    bNumInterfaces         1
    bConfigurationValue    1
    iConfiguration         0
    bmAttributes           0x80
    (Bus Powered)
    MaxPower               500mA
Interface Descriptor:
    bLength                9
    bDescriptorType        4

```

```

bInterfaceNumber      0
bAlternateSetting     0
bNumEndpoints        3
bInterfaceClass       255 Vendor Specific Class
bInterfaceSubClass    255 Vendor Specific Subclass
bInterfaceProtocol    255 Vendor Specific Protocol
iInterface            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x81 EP 1 IN
  bmAttributes         1
    Transfer Type      Isochronous
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0000 1x 0 bytes
  bInterval            1
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x82 EP 2 IN
  bmAttributes         2
    Transfer Type      Bulk
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0200 1x 512 bytes
  bInterval            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x83 EP 3 IN
  bmAttributes         3
    Transfer Type      Interrupt
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0001 1x 1 bytes
  bInterval            10
Interface Descriptor:
  bLength              9
  bDescriptorType      4
  bInterfaceNumber     0
  bAlternateSetting    1
  bNumEndpoints        3
  bInterfaceClass       255 Vendor Specific Class
  bInterfaceSubClass    255 Vendor Specific Subclass
  bInterfaceProtocol    255 Vendor Specific Protocol
  iInterface            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x81 EP 1 IN
  bmAttributes         1
    Transfer Type      Isochronous
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0080 1x 128 bytes
  bInterval            1
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x82 EP 2 IN
  bmAttributes         2
    Transfer Type      Bulk
    Synch Type         None
    Usage Type         Data
  wMaxPacketSize      0x0200 1x 512 bytes
  bInterval            0
Endpoint Descriptor:
  bLength              7
  bDescriptorType      5
  bEndpointAddress     0x83 EP 3 IN
  bmAttributes         3

```

```

    Transfer Type          Interrupt
    Synch Type            None
    Usage Type            Data
    wMaxPacketSize        0x0001 1x 1 bytes
    bInterval              10
Interface Descriptor:
  bLength                  9
  bDescriptorType          4
  bInterfaceNumber         0
  bAlternateSetting        2
  bNumEndpoints            3
  bInterfaceClass          255 Vendor Specific Class
  bInterfaceSubClass       255 Vendor Specific Subclass
  bInterfaceProtocol       255 Vendor Specific Protocol
  iInterface                0
Endpoint Descriptor:
  bLength                  7
  bDescriptorType          5
  bEndpointAddress         0x81 EP 1 IN
  bmAttributes              1
    Transfer Type          Isochronous
    Synch Type             None
    Usage Type             Data
  wMaxPacketSize          0x0100 1x 256 bytes
  bInterval                1
Endpoint Descriptor:
  bLength                  7
  bDescriptorType          5
  bEndpointAddress         0x82 EP 2 IN
  bmAttributes              2
    Transfer Type          Bulk
    Synch Type             None
    Usage Type             Data
  wMaxPacketSize          0x0200 1x 512 bytes
  bInterval                0
Endpoint Descriptor:
  bLength                  7
  bDescriptorType          5
  bEndpointAddress         0x83 EP 3 IN
  bmAttributes              3
    Transfer Type          Interrupt
    Synch Type             None
    Usage Type             Data
  wMaxPacketSize          0x0001 1x 1 bytes
  bInterval                10
Interface Descriptor:
  bLength                  9
  bDescriptorType          4
  bInterfaceNumber         0
  bAlternateSetting        3
  bNumEndpoints            3
  bInterfaceClass          255 Vendor Specific Class
  bInterfaceSubClass       255 Vendor Specific Subclass
  bInterfaceProtocol       255 Vendor Specific Protocol
  iInterface                0
Endpoint Descriptor:
  bLength                  7
  bDescriptorType          5
  bEndpointAddress         0x81 EP 1 IN
  bmAttributes              1
    Transfer Type          Isochronous
    Synch Type             None
    Usage Type             Data
  wMaxPacketSize          0x0180 1x 384 bytes
  bInterval                1
Endpoint Descriptor:
  bLength                  7
  bDescriptorType          5
  bEndpointAddress         0x82 EP 2 IN
  bmAttributes              2
    Transfer Type          Bulk
    Synch Type             None

```



```

Usage Type          Data
wMaxPacketSize     0x0200 1x 512 bytes
bInterval          0
Endpoint Descriptor:
bLength            7
bDescriptorType    5
bEndpointAddress   0x83 EP 3 IN
bmAttributes       3
  Transfer Type    Interrupt
  Synch Type      None
  Usage Type      Data
wMaxPacketSize     0x0001 1x 1 bytes
bInterval          10
Interface Descriptor:
bLength            9
bDescriptorType    4
bInterfaceNumber   0
bAlternateSetting  4
bNumEndpoints     3
bInterfaceClass    255 Vendor Specific Class
bInterfaceSubClass 255 Vendor Specific Subclass
bInterfaceProtocol 255 Vendor Specific Protocol
iInterface         0
Endpoint Descriptor:
bLength            7
bDescriptorType    5
bEndpointAddress   0x81 EP 1 IN
bmAttributes       1
  Transfer Type    Isochronous
  Synch Type      None
  Usage Type      Data
wMaxPacketSize     0x0200 1x 512 bytes
bInterval          1
Endpoint Descriptor:
bLength            7
bDescriptorType    5
bEndpointAddress   0x82 EP 2 IN
bmAttributes       2
  Transfer Type    Bulk
  Synch Type      None
  Usage Type      Data
wMaxPacketSize     0x0200 1x 512 bytes
bInterval          0
Endpoint Descriptor:
bLength            7
bDescriptorType    5
bEndpointAddress   0x83 EP 3 IN
bmAttributes       3
  Transfer Type    Interrupt
  Synch Type      None
  Usage Type      Data
wMaxPacketSize     0x0001 1x 1 bytes
bInterval          10
Interface Descriptor:
bLength            9
bDescriptorType    4
bInterfaceNumber   0
bAlternateSetting  5
bNumEndpoints     3
bInterfaceClass    255 Vendor Specific Class
bInterfaceSubClass 255 Vendor Specific Subclass
bInterfaceProtocol 255 Vendor Specific Protocol
iInterface         0
Endpoint Descriptor:
bLength            7
bDescriptorType    5
bEndpointAddress   0x81 EP 1 IN
bmAttributes       1
  Transfer Type    Isochronous
  Synch Type      None
  Usage Type      Data
wMaxPacketSize     0x02a8 1x 680 bytes

```

```

    bInterval                1
Endpoint Descriptor:
    bLength                  7
    bDescriptorType          5
    bEndpointAddress         0x82 EP 2 IN
    bmAttributes              2
        Transfer Type        Bulk
        Synch Type           None
        Usage Type           Data
    wMaxPacketSize           0x0200 1x 512 bytes
    bInterval                0
Endpoint Descriptor:
    bLength                  7
    bDescriptorType          5
    bEndpointAddress         0x83 EP 3 IN
    bmAttributes              3
        Transfer Type        Interrupt
        Synch Type           None
        Usage Type           Data
    wMaxPacketSize           0x0001 1x 1 bytes
    bInterval                10
Interface Descriptor:
    bLength                  9
    bDescriptorType          4
    bInterfaceNumber         0
    bAlternateSetting        6
    bNumEndpoints           3
    bInterfaceClass          255 Vendor Specific Class
    bInterfaceSubClass       255 Vendor Specific Subclass
    bInterfaceProtocol       255 Vendor Specific Protocol
    iInterface               0
Endpoint Descriptor:
    bLength                  7
    bDescriptorType          5
    bEndpointAddress         0x81 EP 1 IN
    bmAttributes              1
        Transfer Type        Isochronous
        Synch Type           None
        Usage Type           Data
    wMaxPacketSize           0x0320 1x 800 bytes
    bInterval                1
Endpoint Descriptor:
    bLength                  7
    bDescriptorType          5
    bEndpointAddress         0x82 EP 2 IN
    bmAttributes              2
        Transfer Type        Bulk
        Synch Type           None
        Usage Type           Data
    wMaxPacketSize           0x0200 1x 512 bytes
    bInterval                0
Endpoint Descriptor:
    bLength                  7
    bDescriptorType          5
    bEndpointAddress         0x83 EP 3 IN
    bmAttributes              3
        Transfer Type        Interrupt
        Synch Type           None
        Usage Type           Data
    wMaxPacketSize           0x0001 1x 1 bytes
    bInterval                10
Interface Descriptor:
    bLength                  9
    bDescriptorType          4
    bInterfaceNumber         0
    bAlternateSetting        7
    bNumEndpoints           3
    bInterfaceClass          255 Vendor Specific Class
    bInterfaceSubClass       255 Vendor Specific Subclass
    bInterfaceProtocol       255 Vendor Specific Protocol
    iInterface               0
Endpoint Descriptor:

```

```

    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x81 EP 1 IN
    bmAttributes     1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x0b84 2x 900 bytes
    bInterval       1
Endpoint Descriptor:
    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x82 EP 2 IN
    bmAttributes     2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x0200 1x 512 bytes
    bInterval       0
Endpoint Descriptor:
    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x83 EP 3 IN
    bmAttributes     3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x0001 1x 1 bytes
    bInterval       10
Interface Descriptor:
    bLength          9
    bDescriptorType  4
    bInterfaceNumber 0
    bAlternateSetting 8
    bNumEndpoints   3
    bInterfaceClass  255 Vendor Specific Class
    bInterfaceSubClass 255 Vendor Specific Subclass
    bInterfaceProtocol 255 Vendor Specific Protocol
    iInterface       0
Endpoint Descriptor:
    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x81 EP 1 IN
    bmAttributes     1
        Transfer Type      Isochronous
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x1400 3x 1024 bytes
    bInterval       1
Endpoint Descriptor:
    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x82 EP 2 IN
    bmAttributes     2
        Transfer Type      Bulk
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x0200 1x 512 bytes
    bInterval       0
Endpoint Descriptor:
    bLength          7
    bDescriptorType  5
    bEndpointAddress 0x83 EP 3 IN
    bmAttributes     3
        Transfer Type      Interrupt
        Synch Type         None
        Usage Type         Data
    wMaxPacketSize  0x0001 1x 1 bytes
    bInterval       10
Device Qualifier (for other device speed):
    bLength          10
    bDescriptorType  6

```

```
bcdUSB                2.00
bDeviceClass          0 (Defined at Interface level)
bDeviceSubClass       0
bDeviceProtocol       0
bMaxPacketSize0      64
bNumConfigurations    1
Device Status:       0x0000
                    (Bus Powered)
```